

MATERIAL SAFETY DATA SHEET

EXPRESSIONART**POURING ACRYLIC BLACK****Issue Date** September 2020**Status** Issued by Oceanic Square Pty Ltd

IMPORTED BY

Company Name: Oceanic Square Pty Ltd
Address: 24 Horizon Drive
Beenleigh, QLD 4207
Australia
Tel: +61 (07) 3442 5800
Email: admin@pricesplus.com.au

Every endeavor has been made to ensure that the information contained in this publication is reliable and offered in good faith. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. Customers are encouraged to conduct their own tests as end user suitability of the product for particular uses is beyond our control.

IDENTIFICATION

Product Name: Acrylic Pouring Paint - Black
Other Names: None allocated
Chemical Name: Proprietary Mixture
Manufacturer's Product Code: None allocated
UN Number: None allocated
Dangerous Goods Class and Subsidiary Risk: None allocated
Hazchem Code: None allocated
Poisons Schedule No.: None allocated

COMPOSITION/INGREDIENT INFORMATION

| Chemical Name | CAS Number: | Proportion (%): |
|----------------------------|--------------------------------|------------------------|
| Distilled Water | 7732-18-5 | 50.00 |
| Atchsol 8061 | 25035-69-2(49%)/7732-18-5(51%) | 37.85 |
| AMP-95 | 124-68-5(88%)/7732-18-5(12%) | 0.20 |
| ACRYSOL ASE-60 thickener | 25212-88-8(27%)/7732-18-5(73%) | 0.60 |
| Hydroxyethylcellulose | 9004-62-0 | 0.30 |
| Texanol (TM) Ester Alcohol | 25265-77-4 | 2.00 |
| Propylene glycol | 57-55-6 | 5.00 |
| ACTICIDE L | 52-51-7 | 0.05 |
| Carbon black | 1333-86-4 | 4.00 |

PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Ointment

MATERIAL SAFETY DATA SHEET

| | |
|--------------------------------|----------------------------|
| Odour: | Ammonia |
| pH: | 9.0-10.0 |
| Boiling Point/range: | 100°C |
| Melting Point/range: | 0°C water |
| Evaporation Rate: | <1 water |
| Flashpoint: | Noncombustible |
| Lower Explosion Limit: | Not Applicable |
| Upper Explosion Limit: | Not Applicable |
| Vapor Pressure: | 2,266.474 Pa at 20°C water |
| Relative Vapor Density: | <1.0 water |
| Solubility in Water: | Dilutable |
| Relative Density: | 1.0-1.20 |
| Viscosity, Dynamic: | 50-400mPa.s |
| Percent Volatility: | 49-51% water |

Note: The physical data presented above are typical values and should not be construed as a specification.

STABILITY AND REACTIVITY

| | |
|----------------------------------|---|
| Stability: | Stable |
| Hazardous Polymerization: | Will not occur |
| Conditions to Avoid: | None known |
| Incompatible Materials: | No known materials which are incompatible with this product |
| Decomposition: | None known |

HAZARDOUS IDENTIFICATION

Primary Routes of Exposure: Inhalation, skin contact, eye contact

Inhalation: Inhalation of vapor or mist can cause irritation of the nose and throat.

Eye Contact: Direct contact with material may cause slight irritation.

Skin Contact: Prolonged or repeated skin contact may cause slight irritation.

FIRST AID MEASURES

Advice: For advice, contact a Poisons Information Centre (Phone within Australia 13 11 26; or a doctor at once).

MATERIAL SAFETY DATA SHEET

| | |
|-----------------------|---|
| Inhalation: | Remove to fresh air. |
| Eyes: | Rinse with plenty of water. If eye irritation persists, consult a doctor. |
| Skin: | Wash with soap and water as a precaution. If skin irritation persists, consult a doctor. |
| Ingestion: | Drink 1-2 glasses of water. Consult a doctor if necessary. Never give anything by mouth to an unconscious person. |
| Safety Points: | Avoid contact with eyes. Avoid contact with skin. Do not ingest. |

EXPOSURE CONTROL/PERSONAL PROTECTION

| | |
|---------------------|---|
| Respiratory: | Use certified respiratory protective equipment meeting AU requirements, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection by measures, methods or procedures of work organization. |
| Skin: | Neoprene gloves may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. |
| Eye: | Safety glasses with side shields. Eye protection must be compatible with respiratory system employed. |
| Other: | Facilities storing or utilizing this material should be equipped with an eyewash facility. Use only in an area provided with appropriate exhaust ventilation. |

FIRE FIGHTING MEASURES

| | |
|---|--|
| Thermal decomposition: | Thermal decomposition may yield acrylic monomers. |
| Extinguishing Media: | Use extinguishing media appropriate for surrounding fire. |
| Specific Fire and Explosion Hazards: | Material can splatter above 100°C/212F. Dried product can burn. |
| Special Instructions: | Fire fighters should wear self-contained breathing apparatus and full protective clothing. |

HANDLING AND STORAGE

MATERIAL SAFETY DATA SHEET

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas.

Storage: Store at 1-49 °C. Monomer vapors can be evolved when material is heated during processing operations. KEEP CLOSED WHEN NOT IN USE. Keep from freezing. Product stability may be affected. STIR WELL BEFORE USE.

ACCIDENTAL RELEASE

Personal Precautions: Use personal protective equipment. Keep people away from and upwind of spill/leak. Material can create slippery conditions.

Environmental Precautions: CAUTION: Keep spills and cleaning run off out of municipal sewers and open bodies of water.

Clean Up: Contain spills immediately with inert materials e.g., sand, earth. Transfer liquid and solid diking material to separate suitable container.

Disposal: Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

OTHER INFORMATION

Toxicological Information: Non-toxic

CONTACT POINT

| ORGANISATION | TELEPHONE | ASK FOR |
|---|--------------------|----------------|
| Poisons Information Centre – Australia Wide | 131126 | |
| Oceanic Square Pty Ltd | +61 (07) 3442 5800 | David Fielding |
| Fire Brigade | 000 | Fire Brigade |
| Police | 000 | Police |
| Ambulance | 000 | Ambulance |

Every endeavor has been made to ensure that the information contained in this publication is reliable and offered in good faith. The above information is based on data available to us and considered to be accurate. The information is not intended as an inducement to bargain and no warranty expressed or implied is made as to its accuracy, reliability or completeness. As the information contained herein may be applied under conditions beyond our control and with which we are unfamiliar, Oceanic Square Pty Ltd accepts no liability for loss, injury or damage arising from reliance upon the information contained in this data sheet or the material to which it refers. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the effects properties and protections, which pertain to their particular conditions. Due care should be taken that the use and disposal of this product is in compliance with appropriate Federal, State, and Local Government regulations.