

# MATERIAL SAFETY DATA SHEET

**EXPRESSIONART****POSTER PAINT GLITTER SILVER****Issue Date** September 2020**Status** Issued by Oceanic Square Pty Ltd

---

**IMPORTED BY**

---

**Company Name:** Oceanic Square Pty Ltd  
**Address:** 24 Horizon Drive  
Beenleigh, QLD 4207  
Australia  
**Tel:** +61 (07) 3442 5800  
**Email:** admin@pricesplus.com.au

Every endeavor has been made to ensure that the information contained in this publication is reliable and offered in good faith. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. Customers are encouraged to conduct their own tests as end user suitability of the product for particular uses is beyond our control.

---

**IDENTIFICATION**

---

**Product Name:** Poster Paint – Glitter Silver  
**Other Names:** Tempera Paint – Glitter Silver  
**Chemical Name:** Proprietary Mixture  
**Manufacturer's Product Code:** None allocated  
**UN Number:** None allocated  
**Dangerous Goods Class and Subsidiary Risk:** None allocated  
**Hazchem Code:** None allocated  
**Poisons Schedule No.:** None allocated

---

**COMPOSITION/INGREDIENT INFORMATION**

---

| <b>Chemical Name</b> | <b>CAS Number:</b>                                   | <b>Proportion (%):</b> |
|----------------------|--|------------------------|
| Distilled Water      | 7732-18-5  | 80.05                  |
| ACTICIDE L           | 52-51-7  | 0.05                   |
| PVP K90              | 9003-39-8(20%)/7732-18-5(80%)                        | 9.00                   |
| ACRYSOL ASE-60       | 124-68-5(88%)/4432-18-5(12%)                         | 5.00                   |
| AMP-95               | 25212-88-8(27%)/7732-18-5(73%)                       | 0.40                   |
| Kaolinnita           | 1318-74-7  | 3.00                   |
| Glitter Powder JCA68 | 25038-59-9(96.5%)/63450-15-7(3%)<br>/7429-90-5(0.5%) | 2.50                   |

# MATERIAL SAFETY DATA SHEET

---

## PHYSICAL AND CHEMICAL PROPERTIES

---

|                                |                |
|--------------------------------|----------------|
| <b>Physical State:</b>         | Ointment       |
| <b>Odour:</b>                  | Ammonia        |
| <b>pH:</b>                     | 9.0-10.0       |
| <b>Boiling Point/range:</b>    | Not Applicable |
| <b>Melting Point/range:</b>    | Not Applicable |
| <b>Evaporation Rate:</b>       | <1 water       |
| <b>Flashpoint:</b>             | Noncombustible |
| <b>Lower Explosion Limit:</b>  | Not Applicable |
| <b>Upper Explosion Limit:</b>  | Not Applicable |
| <b>Vapor Pressure:</b>         | Not Applicable |
| <b>Relative Vapor Density:</b> | Not Applicable |
| <b>Solubility in Water:</b>    | Not Applicable |
| <b>Relative Density:</b>       | Not Applicable |
| <b>Viscosity, Dynamic:</b>     | Not Applicable |
| <b>Percent Volatility:</b>     | Not Applicable |

**Note:** The physical data presented above are typical values and should not be construed as a specification.

---

## STABILITY AND REACTIVITY

---

|                                  |   |
|----------------------------------|---|
| <b>Stability:</b>                | Stable  |
| <b>Hazardous Polymerization:</b> | Will not occur  |
| <b>Conditions to Avoid:</b>      | None known  |
| <b>Incompatible Materials:</b>   | No known materials which are incompatible with this product |
| <b>Decomposition:</b>            | None known  |

---

## HAZARDOUS IDENTIFICATION

---

**Primary Routes of Exposure:** Inhalation, skin contact, eye contact

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | Inhalation of vapor or mist can cause irritation of the nose and throat. |
| <b>Eye Contact:</b>  | Direct contact with material may cause slight irritation.                |
| <b>Skin Contact:</b> | Prolonged or repeated skin contact may cause slight irritation.          |

# MATERIAL SAFETY DATA SHEET

---

## FIRST AID MEASURES

---

|                       |   |
|-----------------------|---|
| <b>Advice:</b>        | For advice, contact a Poisons Information Centre (Phone within Australia 13 11 26; or a doctor at once).          |
| <b>Inhalation:</b>    | Remove to fresh air.  |
| <b>Eyes:</b>          | Rinse with plenty of water. If eye irritation persists, consult a doctor.   |
| <b>Skin:</b>          | Wash with soap and water as a precaution. If skin irritation persists, consult a doctor.                          |
| <b>Ingestion:</b>     | Drink 1-2 glasses of water. Consult a doctor if necessary. Never give anything by mouth to an unconscious person. |
| <b>Safety Points:</b> | Avoid contact with eyes. Avoid contact with skin. Do not ingest.  |

---

## EXPOSURE CONTROL/PERSONAL PROTECTION

---

|                     |   |
|---------------------|---|
| <b>Respiratory:</b> | Use certified respiratory protective equipment meeting AU requirements, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection by measures, methods or procedures of work organization. |
| <b>Skin:</b>        | Neoprene gloves may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection.  |
| <b>Eye:</b>         | Safety glasses with side shields. Eye protection must be compatible with respiratory system employed.   |
| <b>Other:</b>       | Facilities storing or utilizing this material should be equipped with an eyewash facility. Use only in an area provided with appropriate exhaust ventilation.   |

---

## FIRE FIGHTING MEASURES

---

|   |   |
|---|---|
| <b>Thermal decomposition:</b>               | Thermal decomposition may yield acrylic monomers.               |
| <b>Extinguishing Media:</b>                 | Use extinguishing media appropriate for surrounding fire.       |
| <b>Specific Fire and Explosion Hazards:</b> | Material can splatter above 100°C/212F. Dried product can burn. |

# MATERIAL SAFETY DATA SHEET

**Special Instructions:** Fire fighters should wear self-contained breathing apparatus and full protective clothing.

---

## HANDLING AND STORAGE

---

**Handling:** Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas.

**Storage:** Store at 1-49 °C. Monomer vapors can be evolved when material is heated during processing operations. KEEP CLOSED WHEN NOT IN USE. Keep from freezing. Product stability may be affected. STIR WELL BEFORE USE.

---

## ACCIDENTAL RELEASE

---

**Personal Precautions:** Use personal protective equipment. Keep people away from and upwind of spill/leak. Material can create slippery conditions.

**Environmental Precautions:** CAUTION: Keep spills and cleaning run off out of municipal sewers and open bodies of water.

**Clean Up:** Contain spills immediately with inert materials e.g., sand, earth. Transfer liquid and solid diking material to separate suitable container.

**Disposal:** Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

---

## OTHER INFORMATION

---

**Toxicological Information:** Non-toxic

---

## CONTACT POINT

---

| ORGANISATION                                | TELEPHONE          | ASK FOR        |
|---|--------------------|----------------|
| Poisons Information Centre – Australia Wide | 131126             |                |
| Oceanic Square Pty Ltd                      | +61 (07) 3442 5800 | David Fielding |
| Fire Brigade                                | 000                | Fire Brigade   |
| Police                                      | 000                | Police         |
| Ambulance                                   | 000                | Ambulance      |

Every endeavor has been made to ensure that the information contained in this publication is reliable and offered in good faith. The above information is based on data available to us and considered to be accurate. The information is not intended as an inducement to bargain and no warranty expressed or implied is made as to its accuracy, reliability or completeness. As the information contained herein may be applied under conditions beyond our control and with which we are unfamiliar, Oceanic Square Pty Ltd accepts no liability for loss, injury or damage arising from reliance upon the information contained in this data sheet or the material to which it refers. This information is furnished upon the condition that

# **MATERIAL SAFETY DATA SHEET**

the persons receiving it shall make their own determinations of the effects properties and protections, which pertain to their particular conditions. Due care should be taken that the use and disposal of this product is in compliance with appropriate Federal, State, and Local Government regulations.